

Pipe Flashing

Square and round base pipe flashing  
For roof pipe flashing

- Pipe opening can be easily customized on job sight utilizing clearly marked pipe diameters on each flashing.
- EPDM and Silicone are both flexible materials, resistant to ultraviolet rays, cracking or weathering.
- Available in EPDM black or gray and silicone red.

- The aluminum base is corrosion resistant and conforms easily to any panel configuration or roof pitch.
- Retrofit flashing is available for piping with welded caps or cross bars.
- Colors available in standard square and round base pipe flashing.

Application

Square Base

Size	Pipe size	Base size
1	1/4 – 2 -3/4"	4-1/2"
2	7/8 – 4"	6"
3	1/4 – 5-3/4"	8"
4	2-3/4 – 7"	10"
5	4 – 8-1/4"	11"
6	4-3/4 – 10"	12"
7	5-1/2 – 11"	14"
8	6-3/4 – 13-1/2"	17"
9	9-1/2 – 20-1/2"	25"
10	12 – 28-1/2"	34"



Round Base

Size	Pipe size	Base Size
1	1/4 – 2-1/2"	4-3/4"
2	1-3/4 – 3"	6-1/4"
3	1/4 – 5"	7-3/4"
4	3 – 6-1/4"	9-1/4"
5	4-1/4 – 7-3/4"	10-3/4"
6	5 – 9"	12-1/4"
7	6 – 11"	14-1/4"
8	7 – 13"	16-1/2"
9	9 – 19"	25-1/2"



Retrofit Square Base

Size	Pipe size	Base Size
1	1/2 – 4"	8-3/16"
2	4 – 9-1/4"	14-1/4"
3	9-1/4 – 16-1/4"	21-1/2"



Retrofit Round Base Zipper

Size	Pipe size	Base Size
1	3/4 – 2-3/4"	4-3/4"
2	2 – 7-1/4"	10-3/4"
3	3-1/4 – 10"	25-1/4"



## Pipe Flashing

Square and round base pipe flashing  
*For roof pipe flashing*

## Material Specifications

Test Type	EPDM	Silicone (Hi-Temp)
Advance ozone resistance test @ 500 pphm	70 Hrs.	70 Hrs.
High temperature:		
Intermittent	+275° F	+500° F
Continuous	+212° F	+437° F
Low temperature:		
Resistance tested to	-65° F	-100° F
Tensile strength	1450 psi	700 psi



## Options

Colors Available