

Blind Rivets

Installation Tools for Blind Rivets

Application

AccuBird
12 Volt Cordless Riveting Tool



Weight: 4.8 lbs. (2.2 kg)
Working Stroke: .79" (20 mm)
Traction Power: 1,900 lbs. (6,500 N)
Power Pack: 12 Volt, rechargeable NiCad / 7.7 Ah
 P/N 7261017
Battery Charger: 110V/50Hz, 80 minute charge time

PowerBird
12 Volt Cordless Riveting Tool



Weight: 4.8 lbs. (2.2 kg)
Working Stroke: .79" (20 mm)
Traction Power: 2,900 lbs. (13,000 N)
Power Pack: 12 Volt, rechargeable NiCad / 2.0 Ah
 P/N 7251092
Battery Charger: 110V/50Hz, 60 minute charge time

RV74G
Electric (AC) Powered Bulb-Tite Tool

• The RV74G is the newest refinement in GESIPA Electric Powered Bulb-tite installation tool that is designed for Metal Building Construction applications. This tool is suited to sidewall panel applications. Attaching the optional 74-EXT extension adapts the RV74G for installing Bulb-tites in roofing applications from a standing position.



Work Capacity: 5/32", 3/16", 1/4" & 9/32" Bulb-tite Rivets*
 *Requires appropriate sized RV8840 series Bulb-tite pulling head.
Weight: 6.5 lbs. w/ pulling head attached
Length: 14" w/o pulling head, 18" w/ pulling head attached
Traction Power: .3,000 lbs.
Work Stroke: Continuous reciprocating .375" per cycle

RV 74-EXT
Pulling Head Extension Unit

• Attachment of the 74 EXT extension unit adapts the RV74G tool for roofing applications. This ergonomic feature enables Bulb-tite installation while standing.



Weight: 1.5 lbs.
Length: 12 13/16" (Extends tool by 12")

Bulb-tite Pulling Heads
RV8840-X (5,6,8,9 Diameter Bulb-tite Rivets)

• RV8840 series pulling heads are designed for use with 6603, 8604, 8605 series Bulb-tite rivets which feature multi-grip type mandrels.
 • These heads are equipped with jaws and tips for specific diameter Bulb-tite rivets. The special Bulb-tite crown-awaging nose tip pivots to align the tip onto the Bulb-tite rivet's head crown for improved bore sealing of installed rivets.



Specify the Bulb-tite rivet diameter when ordering.

Weight: 0.5 lbs.
Length: 6 1/16"

RV24RE
Bulb-tite Removal Tool



Designed for use with Aluminum Bulb-tite rivets, the tool greatly simplifies rivet removal in repair operations. The specially ground jaws cut rivet heads off cleanly without damage to the application material.

GESIPA® Power Installation Tools

Taurus 1

HYDRO-PNEUMATIC POWER RIVETING TOOL

WORK CAPACITY:

1/8" \varnothing in all materials

WEIGHT: 2.87 lbs.

PULLING STRENGTH:

1,150 lbs. @ 90 psi

WORKING STROKE:

.590 in.

FEATURES:

- Nose tips for each rivet diameter are stored in tool's base
- Same hydraulic section as the Taurus 2 ensures long tool life and reduced maintenance
- Suspension loop retracts into tool body



Taurus 2

HYDRO-PNEUMATIC POWER RIVETING TOOL

WORK CAPACITY: Up to 3/16" \varnothing in all materials

WEIGHT: 3.75 lbs.

PULLING STRENGTH:

2,500 lbs. @ 90 psi

WORKING STROKE:

.709 in.

FEATURES:

- New 3-piece jaw design increases jaw life — reducing service costs
- Integrated mandrel collection system with grip release shutoff — conserves compressed air resources
- Padded ergonomic tool grip enhances comfort — lowers operator fatigue



Taurus 3

HYDRO-PNEUMATIC POWER RIVETING TOOL

WORK CAPACITY: Up to 1/4" \varnothing in all materials and 9/32" Alum BT

WEIGHT: 4.19 lbs.

PULLING STRENGTH:

3,900 lbs. @ 90 psi

WORKING STROKE:

.984 in.

FEATURES:

- Taurus 3 is up to 40% lighter than comparable tools in this power range
- Long working stroke installs multi-grip rivets in a single stroke
- Reliable exhaust-air mandrel ejection with large collector and safety interlock



Taurus 4

HYDRO-PNEUMATIC POWER RIVETING TOOL

WORK CAPACITY: Up to 1/4" \varnothing structural blind rivets and 9/32" Alum BT

WEIGHT: 4.4 lbs.

PULLING STRENGTH:

5,500 lbs. @ 90 psi

WORKING STROKE:

.750 in.

FEATURES:

- Taurus 4 offers the high pulling force required for many of today's 1/4" diameter structural blind rivets

